


DB M 1 255 (961 120)


- Coordinated spark-gap-based lightning current arrester consisting of a base part and plug-in protection module
- Maximum system availability due to RADAX Flow follow current limitation
- Directly coordinated with DEHNguard surge protective devices without additional cable length



Figure without obligation



Basic circuit diagram DB M 1 255



Dimension drawing DB M 1 255

Coordinated modular single-pole lightning current arrester with high follow current limitation

Type	DB M 1 255
Part No.	961 120
SPD according to EN 61643-11	Type 1
SPD according to IEC 61643-1/-11	Class I
Max. continuous operating a.c. voltage (U_C)	255 V
Lightning impulse current (10/350 μ s) (I_{imp})	50 kA
Specific energy (W/R)	625.00 kJ/ohms
Nominal discharge current (8/20 μ s) (I_n)	50 kA
Voltage protection level (U_P)	≤ 2.5 kV
Follow current extinguishing capability a.c. (I_R)	50 kA _{rms}
Follow current limitation/Selectivity	no tripping of a 32 A gL/gG fuse up to 50 kA _{rms} (prosp.)
Response time (t_A)	≤ 100 ns
Max. backup fuse (L) up to $I_K = 50$ kA _{rms} ($t_a \leq 0.2$ s)	500 A gL/gG
Max. backup fuse (L) up to $I_K = 50$ kA _{rms} ($t_a \leq 5$ s)	315 A gL/gG
Max. backup fuse (L-L')	125 A gL/gG
Temporary overvoltage (TOV) (U_T)	440 V / 5 sec.
TOV characteristic	withstand
Operating temperature range (parallel connection) (T_{UP})	-40°C...+80°C
Operating temperature range (series connection) (T_{US})	-40°C...+60°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (L/N, L'/N', N/PE (N)) (min.)	10 mm ² solid/flexible
Cross-sectional area (L/N, N/PE(N)) (max.)	50 mm ² stranded/35 mm ² flexible
Cross-sectional area (L'/N') (max.)	35 mm ² stranded/25 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	2 module(s), DIN 43880
Approvals	VDE, KEMA, UL
Extended technical data:	Use in installations with prospective short-circuit currents of more than 50 kA_{rms} (tested by VDE)
- Maximum prospective short-circuit current	100 kA _{rms} (220 kA _{peak})
- Limitation/extinction of mains follow currents	up to 100 kA _{rms} (220 kA _{peak})
- Max. backup fuse (L) up to $I_K = 100$ kA _{rms} ($t_a \leq 0.2$ s)	500 A gL/gG
- Max. backup fuse (L) up to $I_K = 100$ kA _{rms} ($t_a \leq 5$ s)	315 A gL/gG
Weight	340 g
Customs tariff number	85363030
GTIN	4013364118614
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.