


ÚHLOVÁ TRUBKOVÁ KABELOVÁ OKA



normální provedení, úhel 90°

materiál: E - Cu trubka

povrch: galvanické pocínování



1


jmenovitý průřez mm ²	svorník Ø	objednávací číslo	rozměr mm							nářadí	 100 ks ~ kg	 balení ks
			d ₁	a	b	d ₂	d ₄	c ₁	l ₃			
6	M 5	41 R/5	3,5	9	10	5,5	6,5	7,5	9	tabulka strana 1.29 – 1.30	0,590	50
	M 6	41 R/6			12	6,5		7,5	10			
	M 8	41 R/8			14	8,5		10	13			
	M 10	41 R/10			17	10,5		12	15			
	M 12	41 R/12			19	13		13	17			
10	M 5	42 R/5	4,5	10	12	5,5	7	6,5	10		0,570	50
	M 6	42 R/6			12	6,5		6,5	10			
	M 8	42 R/8			15	8,5		10	13			
	M 10	42 R/10			17	10,5		12	15			
	M 12	42 R/12			19	13		13	18			
16	M 5	43 R/5	5,5	13	12	5,5	8,5	7,5	10		1,010	50
	M 6	43 R/6			12	6,5		7,5	11			
	M 8	43 R/8			15	8,5		10	13			
	M 10	43 R/10			17	10,5		12	15			
	M 12	43 R/12			19	13		13	18			
25	M 5	44 R/5	7	15	14	5,5	10	7,5	11		1,400	25
	M 6	44 R/6			14	6,5		7,5	11			
	M 8	44 R/8			16	8,5		10	13			
	M 10	44 R/10			18	10,5		12	15			
	M 12	44 R/12			19	13		13	18			
	M 14	44 R/14			21	15		14,5	20			
35	M 6	45 R/6	8,5	17	17	6,5	12	7,5	11		2,050	25
	M 8	45 R/8			17	8,5		10	13			
	M 10	45 R/10			19	10,5		12	15			
	M 12	45 R/12			21	13		13	18			
	M 14	45 R/14			21	15		14,5	20			
	M 16	45 R/16			26	17		16	22			
50	M 6	46 R/6	10	19	20	6,5	14	10	13		3,340	25
	M 8	46 R/8			20	8,5		10	13			
	M 10	46 R/10			20	10,5		12	16			
	M 12	46 R/12			23	13		13	18			
	M 14	46 R/14			23	15		14,5	20			
	M 16	46 R/16			28	17		16	22			
	M 20	46 R/20			30	21		19	24			
70	M 6	47 R/6	12	21	23	6,5	16,5	10	13		4,900	25
	M 8	47 R/8			23	8,5		10	14			
	M 10	47 R/10			23	10,5		12	16			
	M 12	47 R/12			23	13		13	18			
	M 14	47 R/14			23	15		14,5	20			
	M 16	47 R/16			28	17		16	22			
	M 20	47 R/20			30	21		19	24			

ÚHLOVÁ TRUBKOVÁ KABELOVÁ OKA

normální provedení, úhel 90°

materiál: E - Cu trubka

povrch: galvanické pocínování



jmenovitý průřez mm ²	svorník Ø	objednávací číslo	rozměr mm							nářadí ~ kg	100 ks ks	balení
			d ₁	a	b	d ₂	d ₄	c ₁	l ₃			
95	M 8	48 R/8	13,5	25	26	8,5	18	12	14	tabulka strana 1.29 – 1.30	5,890 5,880 5,930 6,030 6,170 6,420	25
	M 10	48 R/10			26	10,5		12	17			
	M 12	48 R/12			26	13		13	18			
	M 14	48 R/14			26	15		14,5	20			
	M 16	48 R/16			28	17		16	22			
	M 20	48 R/20			36	21		22	24			
120	M 8	49 R/8	15	26	28	8,5	19,5	14	16		7,260 7,300 7,190 7,300 7,350 7,600	10
	M 10	49 R/10			28	10,5		14	17			
	M 12	49 R/12			28	13		14	18			
	M 14	49 R/14			28	15		15	20			
	M 16	49 R/16			30	17		16	22			
	M 20	49 R/20			36	21		22	24			
150	M 8	50 R/8	16,5	30	31	8,5	21	14	16		8,410 8,270 8,340 8,520 8,620 9,100	10
	M 10	50 R/10			31	10,5		14	17			
	M 12	50 R/12			31	13		15	18			
	M 14	50 R/14			31	15		15	20			
	M 16	50 R/16			31	17		16	22			
	M 20	50 R/20			36	21		22	24			
185	M 10	51 R/10	19	30	35	10,5	24	18	22		12,170 11,970 11,770 11,530 12,000	10
	M 12	51 R/12			35	13		18	22			
	M 14	51 R/14			35	15		18	22			
	M 16	51 R/16			35	17		18	22			
	M 20	51 R/20			39	21		22	24			
	240	M 10			52 R/10	21	35	39	10,5			
M 12		52 R/12	39	13				21,5	22			
M 14		52 R/14	39	15				21,5	22			
M 16		52 R/16	39	17				21,5	22			
M 20		52 R/20	39	21				21,5	24			
300		M 12	53 R/12	23,5	44			43	13	29,5	24	24
	M 14	53 R/14	43			15		24	24			
	M 16	53 R/16	43			17		24	24			
	M 20	53 R/20	43			21		24	24			
	400	M 12	54 R/12			27	44	49	13	34	24	24
M 14		54 R/14	49	15				24	24			
M 16		54 R/16	49	17				24	24			
M 20		54 R/20	49	21				24	24			





ÚHLOVÁ TRUBKOVÁ KABELOVÁ OKA



normální provedení, úhel 45°

materiál: E - Cu trubka

povrch: galvanické pocínování



1


jmenovitý průřez mm ²	svorník Ø	objednávací číslo	rozměr mm							nářadí	 100 ks ~ kg	 balení ks		
			d ₁	a	b	d ₂	d ₄	c ₁	l ₃					
6	M 5	41 R/5-45	3,5	9	10	5,5	6,5	7,5	9	tabulka strana 1.29 – 1.30	0,600	50		
	M 6	41 R/6-45			12	6,5							10	
	M 8	41 R/8-45			14	8,5							10	13
	M 10	41 R/10-45			17	10,5							12	15
	M 12	41 R/12-45			19	13							13	17
10	M 5	42 R/5-45	4,5	10	12	5,5	7	6,5	10		0,570	50		
	M 6	42 R/6-45			12	6,5							6,5	10
	M 8	42 R/8-45			15	8,5							10	13
	M 10	42 R/10-45			17	10,5							12	15
	M 12	42 R/12-45			19	13							13	18
16	M 5	43 R/5-45	5,5	13	12	5,5	8,5	7,5	10		1,010	50		
	M 6	43 R/6-45			12	6,5							7,5	11
	M 8	43 R/8-45			15	8,5							10	13
	M 10	43 R/10-45			17	10,5							12	15
	M 12	43 R/12-45			19	13							13	18
25	M 5	44 R/5-45	7	15	14	5,5	10	7,5	11		1,400	25		
	M 6	44 R/6-45			14	6,5							7,5	11
	M 8	44 R/8-45			16	8,5							10	13
	M 10	44 R/10-45			18	10,5							12	15
	M 12	44 R/12-45			19	13							13	18
	M 14	44 R/14-45			21	15							14,5	20
35	M 6	45 R/6-45	8,5	17	17	6,5	12	7,5	11		2,050	25		
	M 8	45 R/8-45			17	8,5							10	13
	M 10	45 R/10-45			19	10,5							12	15
	M 12	45 R/12-45			21	13							13	18
	M 14	45 R/14-45			21	15							14,5	20
	M 16	45 R/16-45			26	17							16	22
50	M 6	46 R/6-45	10	19	20	6,5	14	10	13		3,430	25		
	M 8	46 R/8-45			20	8,5							10	13
	M 10	46 R/10-45			20	10,5							12	16
	M 12	46 R/12-45			23	13							13	18
	M 14	46 R/14-45			23	15							14,5	20
	M 16	46 R/16-45			28	17							16	22
	M 20	46 R/20-45			30	21							19	24
70	M 6	47 R/6-45	12	21	23	6,5	16,5	10	13		5,060	25		
	M 8	47 R/8-45			23	8,5							10	14
	M 10	47 R/10-45			23	10,5							12	16
	M 12	47 R/12-45			23	13							13	18
	M 14	47 R/14-45			23	15							14,5	20
	M 16	47 R/16-45			28	17							16	22
	M 20	47 R/20-45			30	21							19	24



ÚHLOVÁ TRUBKOVÁ KABELOVÁ OKA

normální provedení, úhel 45°

materiál: E - Cu trubka

povrch: galvanické pocínování



jmenovitý průřez mm ²	svorník Ø	objednávací číslo	rozměr mm							nářadí	 100 ks ~ kg	 balení ks
			d ₁	a	b	d ₂	d ₄	c ₁	l ₃			
95	M 8	48 R/8-45	13,5	25	26	8,5	18	12	14	tabulka strana 1.29 – 1.30	6,190 5,700 6,670 6,600 6,780 6,800	25
	M 10	48 R/10-45			26	10,5		12	17			
	M 12	48 R/12-45			26	13		13	18			
	M 14	48 R/14-45			26	15		14,5	20			
	M 16	48 R/16-45			28	17		16	22			
	M 20	48 R/20-45			36	21		22	24			
120	M 8	49 R/8-45	15	26	28	8,5	19,5	14	16		7,920 7,990 7,960 7,940 8,260 8,200	10
	M 10	49 R/10-45			28	10,5		14	17			
	M 12	49 R/12-45			28	13		14	18			
	M 14	49 R/14-45			28	15		15	20			
	M 16	49 R/16-45			30	17		16	22			
	M 20	49 R/20-45			36	21		22	24			
150	M 8	50 R/8-45	16,5	30	31	8,5	21	14	16		9,000 9,150 8,750 9,200 9,220 9,260	10
	M 10	50 R/10-45			31	10,5		14	17			
	M 12	50 R/12-45			31	13		15	18			
	M 14	50 R/14-45			31	15		15	20			
	M 16	50 R/16-45			31	17		16	22			
	M 20	50 R/20-45			36	21		22	24			
185	M 10	51 R/10-45	19	30	35	10,5	24	18	22		13,300 13,320 13,400 12,800 13,100	10
	M 12	51 R/12-45			35	13		18	22			
	M 14	51 R/14-45			35	15		18	22			
	M 16	51 R/16-45			35	17		18	22			
	M 20	51 R/20-45			39	21		22	24			
	240	M 10			52 R/10-45	21	35	39	10,5			
M 12		52 R/12-45	39	13				21,5	22			
M 14		52 R/14-45	39	15				21,5	22			
M 16		52 R/16-45	39	17				21,5	22			
M 20		52 R/20-45	39	21				21,5	24			
300		M 12	53 R/12-45	23,5	44			43	13	29,5	24	24
	M 14	53 R/14-45	43			15		24	24			
	M 16	53 R/16-45	43			17		24	24			
	M 20	53 R/20-45	43			21		24	24			
400	M 12	54 R/12-45	27	44	49	13	34	24	24		34,000 33,400 34,280 31,800	5
	M 14	54 R/14-45			49	15		24	24			
	M 16	54 R/16-45			49	17		24	24			
	M 20	54 R/20-45			49	21		24	24			

