


STÁČENÁ KABELOVÁ OKA

prstencový tvar

DIN 46234

materiál: E - Cu

povrch: galvanické pocínování



jmenovitý průřez mm ²	jmenovitá velikost podle DIN	obj. číslo	rozměr mm						nářadí	100 ks ~ kg	balení ks							
			d ₁	d ₂	b	l	a	s										
0,5 – 1	2,5 – 1	1620/2,5	1,6	2,8	6	11	5	0,8	tabulka strana 4.21 – 4.22	0,060	100							
	3 – 1	1620/3		3,2	6	11												
	3,5 – 1	1620/3,5		3,7	6	11												
	4 – 1	1620/4		4,3	8	12												
	5 – 1	1620/5		5,3	10	13												
	6 – 1*	1620/6		6,5	11	15												
	8 – 1*	1620/8		8,4	14	17												
	10 – 1*	1620/10		10,5	18	19												
1,5 – 2,5	3 – 2,5	1630/3	2,3	3,2	6	11	5	0,8		0,065	100							
	3,5 – 2,5	1630/3,5		3,7	6	11												
	4 – 2,5	1630/4		4,3	8	12												
	5 – 2,5	1630/5		5,3	10	14												
	6 – 2,5	1630/6		6,5	11	16												
	8 – 2,5	1630/8		8,4	14	17												
	10 – 2,5*	1630/10		10,5	15	17												
	12 – 2,5*	1630/12		13	18	19												
4 – 6	4 – 6	1650/4	3,6	4,3	8	14	6	1,0		0,140	100							
	5 – 6	1650/5		5,3	10	15												
	6 – 6	1650/6		6,5	11	16												
	8 – 6	1650/8		8,4	14	19												
	10 – 6	1650/10		10,5	18	21												
	12 – 6*	1650/12		13	18	21												
	10	5 – 10		1652/5	4,5	5,3						10	16	8	1,1		0,230	100
		6 – 10		1652/6		6,5						11	17					
8 – 10		1652/8	8,4	14		20												
10 – 10		1652/10	10,5	18		21												
12 – 10		1652/12	13	22		23												
16	5 – 16	1653/5	5,8	5,3	11	20	10	1,2		0,390	100							
	6 – 16	1653/6		6,5	11	20												
	8 – 16	1653/8		8,4	14	22												
	10 – 16	1653/10		10,5	18	24												
	12 – 16	1653/12		13	22	26												
25	5 – 25	1654/5	7,5	5,3	12	25	11	1,5		0,750	100							
	6 – 25	1654/6		6,5	12	25												
	8 – 25	1654/8		8,4	16	25												
	10 – 25	1654/10		10,5	18	26												
	12 – 25	1654/12		13	22	31												
	16 – 25	1654/16		17	28	35												
35	6 – 35	1655/6	9	6,5	15	26	12	1,6		1,010	100							
	8 – 35	1655/8		8,4	16	26												
	10 – 35	1655/10		10,5	18	27												
	12 – 35	1655/12		13	22	31												
	16 – 35	1655/16		17	28	36												

* nenormalizováno


STÁČENÁ KABELOVÁ OKA



prstencový tvar

DIN 46234

materiál: E - Cu

povrch: galvanické pocínování



jmenovitý průřez mm ²	jmenovitá velikost podle DIN	obj. číslo	rozměr mm						nářadí	 100 ks ~ kg	 balení ks
			d ₁	d ₂	b	l	a	s			
50	6 - 50	1656/6	11	6,5	18	34	16	1,8	tabulka strana 4.21 - 4.22	1,650	100
	8 - 50	1656/8		8,4	18	34				1,650	
	10 - 50	1656/10		10,5	18	34				1,600	
	12 - 50	1656/12		13	22	36				1,800	
	16 - 50	1656/16		17	28	40				2,100	
70	6 - 70	1657/6	13	6,5	22	38	18	2		2,600	50
	8 - 70	1657/8		8,4	22	38				2,500	
	10 - 70	1657/10		10,5	22	38				2,500	
	12 - 70	1657/12		13	22	38				2,400	
	16 - 70	1657/16		17	28	42				2,700	
95	8 - 95	1658/8	15	8,4	24	42	20	2,5		4,300	50
	10 - 95	1658/10		10,5	24	42				4,100	
	12 - 95	1658/12		13	24	42				3,900	
	16 - 95	1658/16		17	28	44				4,100	
120	8 - 120	1659/8	17	8,4	24	44	22	3		5,601	50
	10 - 120	1659/10		10,5	24	44				5,600	
	12 - 120	1659/12		13	24	44				5,400	
	16 - 120	1659/16		17	28	48				5,800	
150	10 - 150	1660/10	19	10,5	30	50	24	3,2		7,600	50
	12 - 150	1660/12		13	30	50				7,600	
	16 - 150	1660/16		17	30	50				7,500	
185	12 - 185	1661/12	21	13	36	50	28	3,5		11,300	50
	16 - 185	1661/16		17	36	50				11,300	
240	12 - 240	1662/12	23,5	13	38	56	32	4		15,900	25
	16 - 240	1662/16		17	38	56				15,900	

