SIEMENS

Product data sheet

3TF2010-0BB4

CONTACTOR, SIZE 00, 3-POLE AC-3, 4KW/400V, SCREW TERMINALS AUXILIARY CONTACT 10E (1NO) DC SOLENOID SYSTEM DC 24V

Abb. ähnlich / similar picture		
General details:		
Number of poles	3	
Size of the contactor	00	
Control circuit:		
Design of activation of the operating mechanism	conventional	
Type of voltage	DC	
Control supply voltage		
 for DC / rated value / minimum 	24 V	
 for DC / rated value / maximum 	24 V	
Main circuit:		
Number of NO contacts / for main contacts	3	
Number of NC contacts / for main contacts	0	
Operating current		
• at AC-3 / at 400 V / rated value	9 A	
• at AC-1 / at 400 V / rated value	16 A	
Service power		
• at AC-3 / at 400 V / rated value	4 kW	
• at AC-1 / at 400 V / rated value	10 kW	
Auxiliary circuit:		

Identification number and letter for switching elements		10 E	
Number of NO contacts / for auxiliary contact		1	
Number of NC contacts / for auxiliary contact		0	
Connection type:			
Design of the electrical connection / for main current circuit		screw-type terminals	
Design of the electrical connection / for auxiliary and control current circuit		screw-type terminals	
Mechanical design:			
Type of fixing/fixation		screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022	
Type of fixing/fixation / Series installation		Yes	
last change: 10		10/31/2006	
Technical Assistance:	Telephone:	+49 (0) 911-895-5900 (8°° - 17°° CET)	
	Fax:	+49 (0) 911-895-5907	
	E-Mail:	technical-assistance@siemens.com	
	Internet:	www.siemens.de/lowvoltage/technical-assistance	